

OS-KSCATALOG-admin Extension

API v2.0 (Aug 29, 2011)

DRAFT



OS-KSCATALOG-admin Extension

API v2.0 (2011-08-29)

Copyright © 2010, 2011 OpenStack All rights reserved.

This document includes details on various operations supported by the OS-KSCATALOG-admin extensions on top of core keystone operations.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Table of Contents

1. About This Extension	1
1.1. Document Change History	2
2. Extension Operations	3
2.1. OS-KSCATALOG Admin Extension	3
2.1.1. Endpoint Template Operations	4
2.1.2. Endpoint Operations	10

List of Tables

2.1. Authentication Header	3
2.2. Parameters	4
2.3. Parameters	7
2.4. Parameters	8
2.5. Parameters	10
2.6. Parameters	11
2.7. Parameters	13
2.8. Parameters	15
2.9. Parameters	16

List of Examples

2.1. List Endpont Templates Response	4
2.2. Add Endpoint Template Request	7
2.3. Add Endpoint Template Response	8
2.4. Get Endpont Template Response	9
2.5. Delete Endpoint Template Request	10
2.6. List Endponts Response	11
2.7. Add Endpoint Request	14
2.8. Add Endpoint Response	14
2.9. Get Endpont Response	15
2.10. Delete Endpoint From a Tenant Request	17

1. About This Extension

Name	OpenStack KSCATALOG Extension
Namespace	http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0
Alias	OS-KSCATALOG-admin
Dependencies	Keystone - OpenStack Identity
Doc Link (PDF)	https://github.com/openstack/keystone/raw/master/keystone/content/admin/OS-KSCATALOG-admin-devguide.pdf
Doc Link (WADL)	https://raw.github.com/openstack/keystone/master/keystone/content/admin/OS-KSCATALOG-admin.wadl
Doc Link (XSD)	https://raw.github.com/openstack/keystone/master/keystone/content/common/xsd/OS-KSCATALOG.xsd
Short Description	OpenStack KSCATALOG Admin Extension to Keystone v2.0 API adds the capability to do CRUD on Endpoint Templates and Endpoints.

1.1. Document Change History

Revision Date	Summary of Changes
Sep. 09, 2011	<ul style="list-style-type: none">Initial release.

2. Extension Operations

Verb	URI	Description
Endpoint Template Operations		
GET	/OS-KSCATALOG/endpointTemplates? serviceId= <i>string</i>	List Endpoint Templates.
POST	/OS-KSCATALOG/endpointTemplates	Add Endpoint Template.
GET	/OS-KSCATALOG/endpointTemplates/ {endpointTemplateId}	Get Endpoint Template.
DELETE	/OS-KSCATALOG/endpointTemplates/ {endpointTemplateId}	Delete a Endpoint Template.
Endpoint Operations		
GET	/tenants/{tenantId}/OS-KSCATALOG/ endpoints	List Endpoints of a Tenant.
POST	/tenants/{tenantId}/OS-KSCATALOG/ endpoints	Add Endpoint to a tenant.
GET	/tenants/{tenantId}/OS-KSCATALOG/ endpoints/{endpointId}	Get Endpoint of a Tenant.
DELETE	/tenants/{tenantId}/OS-KSCATALOG/ endpoints/{endpointId}	Delete a Endpoint from a Tenant.

2.1. OS-KSCATALOG Admin Extension

Extension operations.

Table 2.1. Authentication Header

Header Type	Name	Value
HTTP/1.1 Request	X-Auth-Token	txfa8426a08eaf

The following calls are supported by API OS-KSCATALOG Extension on top of Keystone Admin 2.0:

Verb	URI	Description
Endpoint Template Operations		
GET	/OS-KSCATALOG/endpointTemplates? serviceId= <i>string</i>	List Endpoint Templates.
POST	/OS-KSCATALOG/endpointTemplates	Add Endpoint Template.
GET	/OS-KSCATALOG/endpointTemplates/ {endpointTemplateId}	Get Endpoint Template.
DELETE	/OS-KSCATALOG/endpointTemplates/ {endpointTemplateId}	Delete a Endpoint Template.
Endpoint Operations		
GET	/tenants/{tenantId}/OS-KSCATALOG/ endpoints	List Endpoints of a Tenant.
POST	/tenants/{tenantId}/OS-KSCATALOG/ endpoints	Add Endpoint to a tenant.
GET	/tenants/{tenantId}/OS-KSCATALOG/ endpoints/{endpointId}	Get Endpoint of a Tenant.
DELETE	/tenants/{tenantId}/OS-KSCATALOG/ endpoints/{endpointId}	Delete a Endpoint from a Tenant.

2.1.1. Endpoint Template Operations

Verb	URI	Description
GET	/OS-KSCATALOG/endpointTemplates? serviceId= <i>string</i>	List Endpoint Templates.
POST	/OS-KSCATALOG/endpointTemplates	Add Endpoint Template.
GET	/OS-KSCATALOG/endpointTemplates/ {endpointTemplateId}	Get Endpoint Template.
DELETE	/OS-KSCATALOG/endpointTemplates/ {endpointTemplateId}	Delete a Endpoint Template.

2.1.1.1. List Endpoint Templates

Verb	URI	Description
GET	/OS-KSCATALOG/endpointTemplates? serviceId= <i>string</i>	List Endpoint Templates.

List Endpoint Templates.

Table 2.2. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
serviceId	query	String. Optional.

Normal Response Code(s)

- endpointTemplates (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.1. List Endpoint Templates Response

```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplates xmlns="http://docs.openstack.org/identity/api/ext/OS-
KSCATALOG/v1.0">
  <endpointTemplate
    id="1"
    region="North"
    global="true"
    type="compute"
    name="Compute"
  />
</endpointTemplates>
```

```

publicURL="https://compute.north.public.com/v1"
internalURL="https://compute.north.internal.com/v1"
enabled="true">
<version
  id="1"
  list="https://compute.north.public.com/"
  info="https://compute.north.public.com/v1"/>
</endpointTemplate>
<endpointTemplate
  id="2"
  region="south"
  type="compute"
  name="Compute"
  publicURL="https://service2.public.com/v1"
  internalURL="https://service2.internal.public.com/v1"
  enabled="false">
<version
  id="1"
  list="https://service1.public.com/"
  info="https://service1.public.com/v1"/>
</endpointTemplate>
<endpointTemplate
  id="3"
  region="DFW"
  global="true"
  type="ext1:service1"
  name="Compute"
  publicURL="https://service1.public.com/v1"
  enabled="true">
<version
  id="1"
  list="https://service1.public.com/"
  info="https://service1.public.com/v1"/>
</endpointTemplate>
<endpointTemplate
  id="4"
  region="ORD"
  type="compute"
  name="Compute"
  publicURL="https://service2.public.com/v1"
  enabled="true">
<version
  id="1"
  list="https://service1.public.com/"
  info="https://service1.public.com/v1"/>
</endpointTemplate>
<endpointTemplate
  id="5"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service3.public.com/v1">
<version
  id="1"
  list="https://service1.public.com/"
  info="https://service1.public.com/v1"/>
</endpointTemplate>
</endpointTemplates>

```

```
{
```

```

"OS-KSCATALOG:endpointsTemplates": [
  {
    "id": 1,
    "region": "North",
    "global": true,
    "type": "compute",
    "publicURL": "https://compute.north.public.com/v1",
    "internalURL": "https://compute.north.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.north.public.com/v1/",
    "versionList": "https://compute.north.public.com/",
    "enabled": true
  },
  {
    "id": 2,
    "region": "South",
    "type": "compute",
    "publicURL": "https://compute.south.public.com/v1",
    "internalURL": "https://compute.south.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.south.public.com/v1/",
    "versionList": "https://compute.south.public.com/",
    "enabled": false
  },
  {
    "id": 3,
    "region": "North",
    "global": true,
    "type": "object-store",
    "publicURL": "https://object-store.north.public.com/v1.0",
    "versionId": "1.0",
    "versionInfo": "https://object-store.north.public.com/v1.0/",
    "versionList": "https://object-store.north.public.com/",
    "enabled": true
  },
  {
    "id": 4,
    "region": "South",
    "type": "object-store",
    "publicURL": "https://object-store.south.public.com/v2",
    "versionId": "2",
    "versionInfo": "https://object-store.south.public.com/v2/",
    "versionList": "https://object-store.south.public.com/",
    "enabled": true
  },
  {
    "id": 5,
    "global": true,
    "type": "OS-DNS:DNS",
    "publicURL": "https://dns.public.com/v3.2",
    "versionId": "1.0",
    "versionInfo": "https://dns.public.com/v1.0/",
    "versionList": "https://dns.public.com/",
    "enabled": true
  }
],
"OS-KSCATALOG:endpointsTemplates_links": []
}

```

2.1.1.2. Add Endpoint Template

Verb	URI	Description
POST	/OS-KSCATALOG/endpointTemplates	Add Endpoint Template.

Add Endpoint Template.

Table 2.3. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.

Normal Response Code(s)

- endpointTemplate (201)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)
- badMediaType(415)

Example 2.2. Add Endpoint Template Request

```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  id="1"
  region="North"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpointTemplate>

{
  "OS-KSCATALOG:endpointTemplate": {
    "id": 1,
    "region": "North",
    "global": true,
```

```

    "type": "compute",
    "publicURL": "https://compute.north.public.com/v1",
    "internalURL": "https://compute.north.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.north.public.com/v1/",
    "versionList": "https://compute.north.public.com/",
    "enabled": true
  }
}

```

Example 2.3. Add Endpoint Template Response

```

<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  id="1"
  region="North"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpointTemplate>

```

```

{
  "OS-KSCATALOG:endpointTemplate": {
    "id": 1,
    "region": "North",
    "global": true,
    "type": "compute",
    "publicURL": "https://compute.north.public.com/v1",
    "internalURL": "https://compute.north.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.north.public.com/v1/",
    "versionList": "https://compute.north.public.com/",
    "enabled": true
  }
}

```

2.1.1.3. Get Endpoint Template

Verb	URI	Description
GET	/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}	Get Endpoint Template.

Get Endpoint Template.

Table 2.4. Parameters

Name	Style	Description
Request parameters		

Name	Style	Description
X-Auth-Token	header	String. Required.
X-Auth-Token	header	String. Required.
endpointTemplateId	templateId	Int. Optional.

Normal Response Code(s)

- endpointTemplate (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.4. Get Endpoint Template Response

```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  id="1"
  region="North"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpointTemplate>
```

```
{
  "OS-KSCATALOG:endpointTemplate": {
    "id": 1,
    "region": "North",
    "global": true,
    "type": "compute",
    "publicURL": "https://compute.north.public.com/v1",
    "internalURL": "https://compute.north.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.north.public.com/v1/",
    "versionList": "https://compute.north.public.com/",
    "enabled": true
  }
}
```

```
}
```

2.1.1.4. Delete Endpoint Template.

Verb	URI	Description
DELETE	/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}	Delete a Endpoint Template.

Delete a Endpoint Template.

Table 2.5. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
X-Auth-Token	header	String. Required.
endpointTemplateId	templateId	Int. Optional.

Normal Response Code(s)

- (204)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.5. Delete Endpoint Template Request

This operation does not require a request body.

2.1.2. Endpoint Operations

Verb	URI	Description
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints	List Endpoints of a Tenant.
POST	/tenants/{tenantId}/OS-KSCATALOG/endpoints	Add Endpoint to a tenant.
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Get Endpoint of a Tenant.
DELETE	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Delete a Endpoint from a Tenant.

2.1.2.1. List Endpoints

Verb	URI	Description
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints	List Endpoints of a Tenant.

List Endpoints of a Tenant.

Table 2.6. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
tenantId	template	String. Optional.

Normal Response Code(s)

- endpoints (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.6. List Endpoints Response

```
<?xml version="1.0" encoding="UTF-8"?>
<endpoints
  xmlns="http://docs.openstack.org/identity/api/v2.0">
  <endpoint
    id="1"
    type="compute"
    name="Compute"
    region="North"
    publicURL="https://compute.north.public.com/v1"
    internalURL="https://compute.north.internal.com/v1"
    adminURL="https://compute.north.internal.com/v1">
    <version
      id="1"
      info="https://compute.north.public.com/v1/"
      list="https://compute.north.public.com/"
    />
  </endpoint>
  <endpoint
    id="2"
    type="compute"
    name="Compute"
```



```

        region="South"
        publicURL="https://compute.north.public.com/v1"
        internalURL="https://compute.north.internal.com/v1"
        adminURL="https://compute.north.internal.com/v1">
        <version
            id="1"
            info="https://compute.north.public.com/v1/"
            list="https://compute.north.public.com/"
        />
    </endpoint>
    <endpoint
        id="3"
        type="compute"
        name="Compute"
        region="East"
        publicURL="https://compute.north.public.com/v1"
        internalURL="https://compute.north.internal.com/v1"
        adminURL="https://compute.north.internal.com/v1"
    />
    <endpoint
        id="4"
        type="compute"
        name="Compute"
        region="West"
        publicURL="https://compute.north.public.com/v1"
        internalURL="https://compute.north.internal.com/v1"
        adminURL="https://compute.north.internal.com/v1">
        <version
            id="1"
            info="https://compute.north.public.com/v1/"
            list="https://compute.north.public.com/"
        />
    </endpoint>
    <endpoint
        id="5"
        type="compute"
        name="Compute"
        region="Global"
        publicURL="https://compute.north.public.com/v1"
        internalURL="https://compute.north.internal.com/v1"
        adminURL="https://compute.north.internal.com/v1">
        <version
            id="1"
            info="https://compute.north.public.com/v1/"
            list="https://compute.north.public.com/"
        />
    </endpoint>
</endpoints>

```

```

{
  "endpoints": [{
    "id": 1,
    "region": "North",
    "type": "compute",
    "publicURL": "https://compute.north.public.com/v1",
    "internalURL": "https://compute.north.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.north.public.com/v1/",
    "versionList": "https://compute.north.public.com/"
  },

```

```
{
  {
    "id":2,
    "region":"South",
    "type":"compute",
    "publicURL":"https://compute.north.public.com/v1",
    "internalURL":"https://compute.north.internal.com/v1",
    "versionId":"1",
    "versionInfo":"https://compute.north.public.com/v1/",
    "versionList":"https://compute.north.public.com/"
  },
  {
    "id":3,
    "region":"East",
    "type":"compute",
    "publicURL":"https://compute.north.public.com/v1",
    "internalURL":"https://compute.north.internal.com/v1",
    "versionId":"1",
    "versionInfo":"https://compute.north.public.com/v1/",
    "versionList":"https://compute.north.public.com/"
  },
  {
    "id":4,
    "region":"West",
    "type":"compute",
    "publicURL":"https://compute.north.public.com/v1",
    "internalURL":"https://compute.north.internal.com/v1",
    "versionId":"1",
    "versionInfo":"https://compute.north.public.com/v1/",
    "versionList":"https://compute.north.public.com/"
  },
  {
    "id":5,
    "region":"Global",
    "type":"compute",
    "publicURL":"https://compute.north.public.com/v1",
    "internalURL":"https://compute.north.internal.com/v1",
    "versionId":"1",
    "versionInfo":"https://compute.north.public.com/v1/",
    "versionList":"https://compute.north.public.com/"
  }
],
"endpoints_links":[]
}
```

2.1.2.2. Add Endpoint

Verb	URI	Description
POST	/tenants/{tenantId}/OS-KSCATALOG/endpoints	Add Endpoint to a tenant.

Add Endpoint to a tenant.

Table 2.7. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.

Name	Style	Description
endpoint	plain	EndpointTemplateWithOnlyId. Optional.
tenantId	template	String. Optional.

Normal Response Code(s)

- endpoint (201)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)
- badMediaType(415)

Example 2.7. Add Endpoint Request

```
<?xml version="1.0" encoding="UTF-8"?>
<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:type="EndpointTemplateWithOnlyId"
  id="1"/>
```

```
{
  "OS-KSCATALOG:endpointTemplate": {
    "id": 1,
  }
}
```

Example 2.8. Add Endpoint Response

```
<?xml version="1.0" encoding="UTF-8"?>
<endpoint
  id="1"
  type="compute"
  name="Compute"
  region="North"
  publicURL="https://compute.north.public.com/v1"
  internalURL="https://compute.north.internal.com/v1"
  adminURL="https://compute.north.internal.com/v1"
  xmlns="http://docs.openstack.org/identity/api/v2.0">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpoint>
```

```
{
```

```
"endpoint": {
  "id": 1,
  "region": "North",
  "type": "compute",
  "publicURL": "https://compute.north.public.com/v1",
  "internalURL": "https://compute.north.internal.com/v1",
  "versionId": "1",
  "versionInfo": "https://compute.north.public.com/v1/",
  "versionList": "https://compute.north.public.com/"
}
```

2.1.2.3. Get Endpoint

Verb	URI	Description
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Get Endpoint of a Tenant.

Get Endpoint of a Tenant.

Table 2.8. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
tenantId	template	String. Optional.
endpointId	template	String. Optional.

Normal Response Code(s)

- endpoint (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.9. Get Endpoint Response

```
<?xml version="1.0" encoding="UTF-8"?>
<endpoint
  id="1"
  type="compute"
  name="Compute"
  region="North"
  publicURL="https://compute.north.public.com/v1"
```

```

        internalURL="https://compute.north.internal.com/v1"
        adminURL="https://compute.north.internal.com/v1"
        xmlns="http://docs.openstack.org/identity/api/v2.0">
        <version
            id="1"
            info="https://compute.north.public.com/v1/"
            list="https://compute.north.public.com/"
        />
    </endpoint>

```

```

{
  "endpoint": {
    "id": 1,
    "region": "North",
    "type": "compute",
    "publicURL": "https://compute.north.public.com/v1",
    "internalURL": "https://compute.north.internal.com/v1",
    "versionId": "1",
    "versionInfo": "https://compute.north.public.com/v1/",
    "versionList": "https://compute.north.public.com/"
  }
}

```

2.1.2.4. Delete Endpoint.

Verb	URI	Description
DELETE	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Delete a Endpoint from a Tenant.

Delete a Endpoint from a Tenant.

Table 2.9. Parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
tenantId	template	String. Optional.
endpointId	template	String. Optional.

Normal Response Code(s)

- (204)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.10. Delete Endpoint From a Tenant Request

This operation does not require a request body.